



Basic Information

Model no	66E7253G	
Range	M7G	-
Туре	Socket	
		smon
Highlights	Max020W	
	A/C: 5V = 3A, 9V = 2.22A. 12V 1.67A	

Installation and maintenance

Cable section admitted	1 - 4mm2
Connection terminals type	Screw connection
IP protection	IP20
Material	Glass+PC
Operating temperature range	0 - 40°C



Simon Electric (APAC)

5th floor, No.1 Building, HongQiao Vanke Center,988 Shenchang Road, Shanghai, China E-mail. info@simon-apac.com www.simon-apac.com



The appearance and color of all products listed in this data sheet are for reference only. Simon reserves the right to modify specification and/or discontinue any product at any time without prior notice.



Installation type

Suitable for flush mounting box (86 type if multigang frame)

Additional information

Rated current	13A
Rated voltage	250V
Quantity per box	10
Box size(mm)	355*95*105
Quantity per carton	100
Carton size(mm)	500*370*230



Simon Electric (APAC)

5th floor, No.1 Building, HongQiao Vanke Center,988 Shenchang Road, Shanghai, China E-mail. info@simon-apac.com www.simon-apac.com



The appearance and color of all products listed in this data sheet are for reference only. Simon reserves the right to modify specification and/or discontinue any product at any time without prior notice.