



See nothing, hear everything

The marine environment is unforgiving. Any equipment has to survive extremes of temperature, salt spray and hosing down. It's little wonder then that most speakers designed for marine applications sacrifice sound quality for ruggedness.

Of course, any Bowers & Wilkins speaker must sound brilliant. So these marine speakers were first designed to match exacting sound quality standards, then the necessary toughness to survive the harsh marine environment was added. Both models boast IP66 ratings when properly installed, and the metal grille and all screws are marine-grade stainless steel. The driver chassis uses a non-corroding rigid polymer and the tweeter dome has a rear support to prevent permanent deformation when hosed down.

Marine 6 and Marine 8 are super-tough to deal with the most demanding installation environments, with Bowers & Wilkins superior, uncompromising audio quality.

Technical Specifications

Description	2-way system
Drive Units	1x Ø25mm (1 in) soft dome tweeter 1x Ø200mm (8 in) polypropylene cone bass/midrange
Frequency range (-6dB)	36Hz – 26kHz
Recommended Amplifier Power	20W – 80W
Sensitivity	88dB (2.83V, 1m)
Nominal Impedance	8Ω (4Ω minimum)
Outer diameter	Ø292mm (11.5 in)
Cut-out diameter	Ø253mm (10 in)
Depth behind surface	93mm (3.7 in)
Protrusion	8mm (0.3 in)
Net weight	1.7kg (3.8 lb)
Pre-mount Kit	PMK C8